

COMMANDS**Primary Action Commands**

```
clear, exec, exit, get, ping, reset, save, set, trace-route, unset
```

List Rules [To TFTP Server]

```
get config [ > tftp <tftp_server> <file_name> ]
```

Get System Information

```
get session info  
get sys-cfg
```

POLICY**Define Policy**

```
set policy id <id> from "<src_zone>" to "<dst_zone>" "<src_host>" "<dst_host>" "<service>" <permit/deny> [log] [count]
```

Add Service To Policy

```
set policy <id>  
set service "<service_name or group>"  
exit
```

Add host to a Policy

```
set policy <id>  
set dst-address "<host_name or group>"  
set src-address "<host_name or group>"  
exit
```

Move Policy

```
set policy move <id1> <before/after> <id2>
```

SERVICES**Add Service**

```
set service "<name>" protocol <tcp/udp/icmp> src-port <port-range> dst-port <port-range>
```

Add To a Service

```
set service "<name>" + [tcp/udp] src-port <port-range> dst-port <port-range>
```

Create Service Group

```
set group service "<service_group>"
```

Add Host to Service Group

```
set group service "<service_group>" add "<host>"
```

ADDRESS**Add Address**

```
set address "<zone>" "<host identifier>" <ip> [netmask if a range] "[comment]"
```

Create Address Group ("Address Book")

```
set group address "<zone>" "<group_name>"
```

Add Host to Address Group

```
set group address "<zone>" "<group_name>" add "<host>"
```

SERIAL SETTINGS

Speed: 9600 Bps

Char Size: 8bit

Parity: None

Stop Bits: 1

Flow Ctrl: None

5XP, 5GT, 500: Straight through serial cable DB9M to DB9F

All Others: RJ-45 Serial cable with DB9F